



Herbicides



Suitable for

Fungicides




Suitable for

Insecticides



Suitable for



1.5÷8 bar



Working pressure

15 bar



Maximum pressure

100°-110°



Spraying angle

Boom



Treatment

ISO
10625

Colour coding

Delrin®



Material

402900xx





Cap







10 pcs.




Blister pack

cod.
+
B1



Mod. Мод.	Cód. Код Kod					l/ha (espaço entre os bicos: 50 cm) л/га (расстояние между распылителями: 50 см) l/ha (odległość między dyszami: 50 cm)							
						6 km/h 6 км/ч	8 km/h 8 км/ч	10 km/h 10 км/ч	12 km/h 12 км/ч	14 km/h 14 км/ч	16 km/h 16 км/ч	18 km/h 18 км/ч	20 km/h 20 км/ч
	CFA11001	110°	2	C	0.33	65	49	39	33	28	24	22	20
			3	M	0.40	80	60	48	40	34	30	27	24
			4	M	0.46	92	69	55	46	39	35	31	28
			5	M	0.52	104	78	62	52	45	39	35	31
	CFA110015	110°	2	C	0.49	98	73	59	49	42	37	33	29
			3	M	0.60	120	90	72	60	51	45	40	36
			4	M	0.69	138	104	83	69	59	52	46	42
			5	M	0.77	154	116	92	77	66	58	51	46
	CFA11002	110°	2	C	0.65	131	98	78	65	56	49	44	39
			3	M	0.80	160	120	96	80	69	60	53	48
			4	M	0.92	184	138	110	92	79	69	61	55
			5	M	1.03	206	155	124	103	88	77	69	62
	CFA110025	110°	2	VC	0.82	163	122	98	82	70	61	54	49
			3	C	1.00	200	150	120	100	86	75	67	60
			4	C	1.15	230	173	138	115	99	86	77	69
			5	M	1.29	258	194	155	129	111	97	86	77
	CFA11003	110°	2	VC	0.98	196	147	118	98	84	73	65	59
			3	C	1.20	240	180	144	120	103	90	80	72
			4	C	1.39	278	209	167	139	119	104	93	83
			5	C	1.55	310	233	186	155	133	116	103	93
	CFA11004	110°	2	VC	1.31	261	196	157	131	112	98	87	78
			3	C	1.60	320	240	192	160	137	120	107	96
			4	C	1.85	370	278	222	185	159	139	123	111
			5	C	2.07	414	311	248	207	177	155	138	124
CFA11005	110°	2	VC	1.63	327	245	196	163	140	122	109	98	
		3	C	2.00	400	300	240	200	171	150	133	120	
		4	C	2.31	462	346	277	231	198	173	154	139	
		5	C	2.58	516	387	310	258	221	193	172	155	
	SFA11006	100°	2	VC	1.96	392	294	235	196	168	147	131	118
			3	VC	2.40	480	360	288	240	206	180	160	144
			4	VC	2.77	554	416	333	277	238	208	185	166
			5	VC	3.10	620	465	372	310	266	232	207	186
	SFA11008	100°	2	VC	2.61	523	392	314	261	224	196	174	157
			3	VC	3.20	640	480	384	320	274	240	213	192
			4	VC	3.70	739	554	443	370	317	277	246	222
			5	VC	4.13	826	620	496	413	354	310	275	248
	SFA11010	100°	2	VC	3.27	653	490	392	327	280	245	218	196
			3	VC	4.00	800	600	480	400	343	300	267	240
			4	VC	4.62	924	693	554	462	396	346	308	277
			5	VC	5.16	1.033	775	620	516	443	387	344	310
	6	VC	5.66	1.131	849	679	566	485	424	377	339		

	DIMENSÕES DAS GOTAS РАЗМЕРЫ КАПЕЛЬ WYMIARY KROPEL	
M	Média-Sредняя-Rednie	217 ÷ 353 µm/мкм
C	Grossa-Kрупная-Grube	354 ÷ 464 µm/мкм
VC	Muito grossa-Очень крупная-Bardzo grube	> 464 µm/мкм

µm = milésimo de milímetro (Ex.: 250µm = 0.25 mm)
 мкм = тысячная доля от миллиметра (например, 250 мкм = 0.25 мм)
 мкм = mikrometr (np.: 250µm = 0.25 mm)